

AV 822 Ravni zaporni ventil iz nerjavečega jekla DN15 do DN200 PN16

AV 825 Ravni zaporni ventil iz nerjavečega jekla DN15 do DN200 PN40

Ohišje: GX5CrNiMo19-11-2 1.4408 Drugi notranji deli: X6CrNiMoTi17-12-2 1.4571

AV 811 Ravni zaporni ventil iz jekla DN15 do DN200

Ohišje: W.Nr. 1.0619

Z dvigajočim se vretenom, vgradna mera po DIN EN558-1
Prirobnice vrtane po DIN 2501 oblika C DIN2526
Ročno kolo iz pločevine.



DN	PN	Prikjučne prirobnice						Ostale mere					Masa [kg]				
		D	g	k	nxd1	b	f	L	L1	d2	H	X					
15	40	95	45	65	4x14	16	2	130	□ 65	125	193,5		3,5				
20	40	105	58	75	4x14	18	2	150	□ 75	125	222,5		5				
25	40	115	68	85	4x14	18	2	160	□ 80	125	225,5		6,5				
32	40	140	78	100	4x18	18	2	180	□ 90	125	225,5		10				
40	40	150	88	110	4x18	18	3	200	□ 95	150	264,5		14				
50	40	165	102	125	4x18	20	3	230	□ 110	150	266,5		15,5				
65	16	185	122	145	4x18	22	3	290	160	200	334		23				
	8x18																
80	16	200	138	160	8x18	20	3	310	162	200	365		30				
	40					24			176		371						
100	16	220	158	180	8x18	20	3	350	202	250	434		48				
	40	235	162	190	8x22	24			220		441						
125	16	250	188	210	8x18	22	3	400	226	400	501		66				
	40	270		220	8x26	26			242		508			X			
150	16	285	212	240	8x22	22	3	480	255	400	602		96				
	25	300	218	250	8x26	28			280		400			585	X		
	40																
200	16	340	268	295	12x22	24	3	600	322	500	698	X	162				
	25	360	278	310	12x26	34			350					500	698	X	169
	40	375	285	320	12x30	34											
250	10	395	320	350	12x22	26	3	730	350	640	890	X					
	16	405	320	355	12x26												
	25	425	335	370	12x30				32	415	500			735			
	40	450	345	385	12x33										38		
300	10	445	370	400	12x22	28	4	850	450	500	805	X					
	16	460	378	410	12x26												

